



工作压力 = 0.5MPa

负荷率 = 100%

单位: N

系列 \ 缸径		缸径																		
		8	10	12	16	20	25	32	40	50	63	80	100	125	160	180	200	250	320	400
10A-5	推力							402	628	981	1559	2513	3927	6136	10053					
	拉力							346	528	792	1369	2268	3682	5734	9425					
10B-5	推力																			
	拉力																			
10Y-1	推力	25	39	57	101	157	245	402	628	981										
	拉力	19	33	42	85	132	206	346	551	881										
10Y-2	推力					157	245	402	628											
	拉力					132	206	346	551											
10A-2	推力													6136	10053		15708	24544		
	拉力													5734	9425		15080	23748		
QG ^A _B	推力							402	628	981	1559	2513	3927	6136	10053		15708	24544	40212	62832
	拉力							346	572	881	1401	2356	3682	5734	9425		15080	22985	37699	59651
QG ^A _B ^b	推力								628	981	1559	2513	3927	6136	10053		15708			
	拉力								471	825	1313	2268	3525	5508	9071		14726			
QGX	推力	25		57	101	157	245	402												
	拉力	21		50	86	132	206	346												
QGC	推力											2513	3927	6136	10053					
	拉力											2111	3299	5154	8494					
JB	推力											2513	3927	6136	10053	12723	15708	24544	40212	62832
	拉力											2160	3574	5508	9425	11742	14726	22619	37032	59651
QGY	推力					157	245	402	628	981	1559	2513	2927							
	拉力					132	206	325	551	825	1402	2268	3682							
QGEW-1	推力					132	206	346	551											
	拉力																			
QGEW-2	推力							346	528	792	1369	2268	3682	5734						
	拉力																			
QGEW-3	推力													5734	9425		15080	23748		
	拉力																			

气缸活塞行程标准系列 (GB2349-80)

单位: (mm)

5	10	15	20	25	30	35	40
45	50	75	100	125	150	200	250
300	350	400	450	500	600	700	800
900	1000	1200	1400	1600	1800	2000	

欢迎用户按标准行程选用,也可自由选择。如超过最大行程,可协商订制。

